## 4"Handheld Thermal Printer

Interfaces: USB, Bluetooth

**Key Features:** 

High reliability with simple operation

Drop rating of 2M (6.6 feet) and operating temperature of -20 to 50c

Stylish design with added option of a belt clip or partition plate

Wide variety of driver and SDK for mobile equipment



## TYPICAL APPLICATIONS

(Not Limited to)

- Measuring Instrument
- PDA / Smart Device
- Barcode
- Labels
- Medical Equipment
- Warehouse



Stanelaw Way, Tanfield Lea Industrial Estate South, Durham, DH9 9XG



+44 (0)1207 290266



sales@martelinstruments.com

## 4" Handheld Thermal Printer

SPECIFICATION	4" Handheld
Printing Method	Thermal line dot printing
Number of dots / line	832
Resolution (dots / mm)	8
Paper Roll Width (mm)	80 /100 / 105 / 112 mm
Outside diameter of paper roll (mm)	83 mm
Character Type	Codepage (17 pages), Katakana character set, User-defined character, Downloaded character, Optional font, JIS 1 <sup>st</sup> and 2 <sup>nd</sup> level Kanji, special characters
Barcode	UPC-A / E, Jan (EAN) 8 / 13, ITF, CODE39, CODABAR, CODE93, CODE128, PDF417, QR Code, Maxicode, Data Matrix, GS1 Databar
Power supply (V)	Option: Specified AC adapter, LI-ion battery
Communication interface	USB, Bluetooth
Input buffer	4k bytes
Cutting type	Tear bar
Operating temperature	-20 to 50C
Dimensions (W x D x H mm)	156 x 152 x 71mm
Mass (g)	Approx 760
Standard	FCC, CE, VCCI
Command	ESC / POS conformity, CPCL conformity, HTML command
Options	AC adapter, Battery pack, Battery charger, AC cable, USB cable, Serial cable, Car charger, Strap
Software	Printer Driver / SDK, Windows CE SDK, Android SDK, iOS SDK, URL Print Agent



Copyright of Martel Instruments. All information correct at time of publication. Specifications subject to change without notice.