



MARTEL INSTRUMENTS

MPP3000 3" Thermal Panel Printer Series

Interfaces: RS232 and USB

Key Features:

Fast & simple paper roll changing via hinged front on the robust moulded enclosure

Prints high resolution text, graphics & barcodes on a range of thermal paper & labels

Adjustable clip mounting or panel screw mounts give flexibility for integration into your device

Easily configured to meet your exact specifications



TYPICAL APPLICATIONS

(Not Limited to)

- Medical Devices
- Industrial Automation
- Voting Machines
- Airport Security
- Weighing
- Analyzing & Testing



Stanelaw Way, Tanfield Lea Industrial Estate South,
Durham, DH9 9XG



+44 (0)1207 290266



sales@martelinstruments.com

MPP3000 Thermal Panel Printer Series

| SPECIFICATION | MPP3000 |
|--------------------------|---|
| Characters per line | 36 (default), 18, 24, 48, 72 |
| Average Print Speed | 7 lines per second |
| Print Width (mm) | 72 mm |
| Paper Roll Width (mm) | 80 mm |
| Paper Roll Diameter (mm) | 60 mm (Approx 35M Length) |
| Character Sets | Extended ASCII, (Code page 437, English, German, Swedish) |
| Character Styling | Bold, Underline & Italics |
| Dots Per Line | 576 |
| Data Input | RS232 & USB |
| Data Buffer | 5 KB as Standard |
| Baud Rate | 600 to 115200 (depending on configuration) |
| Power Supply | 5VDC or 10-35VDC |
| Panel Cut Out | 98.5 x 85 mm |
| Weight | Approx. 386.5g (Including Paper) |
| Operating Temperature | 0 – 50 C |
| Paper Out Detection | Yes |
| Printer Drivers | Microsoft Windows & Linux |



MARTEL INSTRUMENTS