

MPP4000 4" Thermal Panel Printer Series

Interfaces: RS232 & USB

Key Features:

Maintenance free, high reliability with quick & easy paper installation

Panel screw mounts give flexibility for integration into your device

Prints high resolution text, graphics & barcodes on a range of thermal paper & labels

Easily configured to meet your exact specifications



TYPICAL APPLICATIONS

(Not Limited to)

- Medical Devices
- Sterilizers
- Voting Machines
- Alarm Panels
- Autoclaves



Stanelaw Way, Tanfield Lea Industrial Estate South, Durham, DH9 9XG



+44 (0)1207 290266



sales@martelinstruments.com

MPP4000 Thermal Panel Printer Series

SPECIFICATION	MPP4000
Characters per line	52, 69, 104
Average Print Speed	7 lines per second
Print Width (mm)	104 mm
Paper Roll Width (mm)	112 mm
Paper Roll Diameter (mm)	55 mm (Approx 30M length)
Character Sets	Extended ASCII, (Code page 437, English, German, Swedish)
Character Styling	Bold, Underline & Italics
Dots Per Line	832
Data Input	RS232 & USB
Data Buffer	5KB as standard
Baud Rate	600 to 115200 (depending on configuration)
Power Supply	5VDC or 10-35VDC
Panel Cut Out	140 x 102.3 mm
Weight	Approx. 523g (Including Paper)
Operating Temperature	0 – 50 C
Paper Out Detection	Yes
Printer Drivers	Microsoft Windows & Linux



Copyright of Martel Instruments. All information correct at time of publication. Specifications subject to change without notice.